

AmerGlas Paintstop

COMMERCIAL GRADE MEDIA FOR PAINT SPRAYING APPLICATIONS

Features and Benefits

- Economical to use
- Removes overspray of all types of paint
- Protects exhaust ducts, fans and motors
- Clean exhaust air is discharged to the atmosphere

Applications

AmerGlas PaintStop media is a commercial grade media designed to remove paint overspray in paintspray cabins.



Configurations

Filter media	Glass fibre
Max. Operating Temperature	150 °C (Green) - 80 °C (Yellow)
Recom. final pressure drop	Subject to optimization of lifecycle costs, max 80 Pa (Green) and 250 Pa (Yellow)
Moisture resistance	100% relative humidity
Media colour	Green or yellow: air inlet side. White: air leaving side
Media property	Green: Dry. Yellow: Sticky

Standard dimensions

Name	Thickness (mm)	Width (mm)	Length (m)	Air Velocity (m/s)	Initial dp (Pa)
AmerGlas Green PaintStop 2	45	2/1/0,75/0,5	20/25/91	1,75	15
AmerGlas Green PaintStop 3	75	2/1/0,75/0,5	20/25/91	1,75	40
AmerGlas Green PaintStop 4	95	2/1/0,75/0,5	20/25	1,75	45
AmerGlas Yellow PaintStop 2	45	2/1/0,75/0,5	20	1,75	40
AmerGlas Yellow PaintStop 4	95	2/1/0,75/0,5	20	1,75	60



Bringing clean air to life:

AAF International
European Headquarters
Odenwaldstrasse 4, 64646 Heppenheim
Tel: +49 (0)6252 69977- 0
aafintl.com

Specifications and performance data contain average values within existing production specification tolerances and are subject to change without prior notice. AAF explicitly rejects any liability for any direct or indirect damage, in the broadest sense, arising from or related to the use and/or interpretation of this information.

©2020 AAF International and its affiliated companies.
PR_101_EN_072020