


VariCel[®] XL HT

COMPACT FILTER



Features and Benefits

- High continuous operating temperature up to 385 °C for improved throughput
- Heat resistant aluminized materials ensure a spall- and flake free finished product
- Mechanically interlocked filter construction providing increased stiffness under tough conditions
- Support bars on air leaving side to guarantee media pack stability
- Fully silicone free product to avoid costly process contaminations
- High dust holding capacity facilitates a longer service life and fewer filter changeouts

Applications

- Second stage or final filtration in hot air systems such as paint drying lines

The VariCel XL HT compact filter is designed to improve air quality in hot air systems such as paint drying lines with a great energy savings level and attractive lifecycle cost.

The air filter is able to handle high continuous temperatures in operation, up to 385 °C. Its sturdy and lightweight construction means that the VariCel XL HT filter is not only less susceptible to damage, but also easy to install and replace.

Consistent Air Quality

The VariCel XL HT filter is available in the EN779:2012 filter class range M6 - F8. This filter is free of silicone to safeguard the air quality during the various steps of the drying process. Furthermore, no adhesives, sealants or glues are used in the construction of the VariCel XL HT filter that could degrade at high temperatures and cause structural damage to the filter or affect the outcome of the drying process.

Improved Process Performance

The VariCel XL HT filter can be applied at high continuous operating temperatures up to 385 °C for improved throughput. The robust aluminized steel construction with faceguards and support bars, and the special designed media pack ensure filter integrity at high airflow and under turbulent operating conditions. The application of aluminized steel ensures a spall- and flake-free finished product.

Environmental Savings

The special designed media pack of the VariCel XL HT filter provides a superior performance and longer service life, which reduces disposal and waste. The media pack has a higher dust holding capacity than traditional design products in a compact 12" depth design. Its compact design ensures a lower weight than market standard 17" depth products with comparable performance levels, resulting in less stress on air filter frames and easier installation.

Beneficial Total Cost of Ownership

The VariCel XL HT filter is designed for use in drying ovens with a maximum energy savings level and attractive lifecycle cost. In continuous operation at a car manufacturer's paint drying line, the VariCel XL HT filter provides up to 40% savings on energy costs compared to traditional designs, which equals a return on investment of less than 18 months. The filter is available in a box, single header and double header construction with the option of a glass rope gasket.



VariCel® XL HT Filter

Standard configuration

Filter medium		Header (optional)	
Material	Fibreglass	Material	Extruded aluminum with provisions for gasket
Pack design	Deep pleat	Depth	20 mm and 25 mm
Separator	Tapered corrugated aluminium	Filter frame	
Gasket		Material	Aluminized steel
Material	Optional: Glass rope gasket	Sealant	Glass media


Product information

Filter	Part number	Dimensions (mm) W x H x D	Filter area (m ²)	Number of pockets or V	Nominal airflow (m ³ /h)	DHC acc. EN779 (g)	EN779:2012 Classification	Initial dp (Pa)	Energy Rating	ISO 16890 Classification	ePM1 (%)	ePM2,5 (%)	ePM10 (%)
VariCel® XL HT F7	20-6387-4202	592 x 592 x 292	13,4	-	3400	375	F7	150	D	ePM1 50%	54	64	82
VariCel® HT XL HT F8	20-8387-4202	592 x 592 x 292	13,4	-	3400	275	F8	170	D	ePM1 65%	68	76	90
VariCel® HT XL HT M6	20-5387-4202	592 x 592 x 292	13,4	-	3400	425	M6	130	E	ePM10 70%	28	42	71

Further dimensions are available on request. Until December 31st 2017 filtration efficiency values are certified according to EN779:2012. From January 1st 2018 filtration efficiency values are certified according to ISO 16890.


VariCel® XL HT Filter

Airflow versus operating resistance



592x592x292 mm - Single/Double header - F8
 592x592x292 mm - Single/Double header - M6
 610x610x292 mm - Single/Double header - F8
 610x610x292 mm - Single/Double header - M6
 610x610x292 mm - Box (no header) - F8
 610x610x292 mm - Box (no header) - M6

Dust holding capacity versus operating resistance



592x592x292 mm - Single/Double header - F8
 592x592x292 mm - Single/Double header - M6
 610x610x292 mm - Single/Double header - F8
 610x610x292 mm - Single/Double header - M6
 610x610x292 mm - Box (no header) - F8
 610x610x292 mm - Box (no header) - M6

VariCel® is a registered trademark of AAF International in the U.S. and other countries.



AAF International
 European Headquarters
 Robert-Bosch-Straße 30-32, 64625 Bensheim
 Tel: +49 6251 80368 - 0, Fax +49 6251 80368 - 20
aafintl.com

AAF International B.V. has a policy of continuous product research and improvement and reserves the right to change design and specifications without notice.

©2018 AAF International and its affiliated companies.
 HT_606_EN_022018